



MIRUM L1400





MIRUM L1400 - STREET LIGHT FIXTURE

DESIGN: STUDIO HAMMER

LIGHT DISTRIBUTION

Direct, symmetrical or asymmetrical light distribution.
Possibility of project adapted light distribution via a wide selection of light distribution lenses.

MATERIALS

Lamp housing: Lamp housing in mold cast aluminium, powder-coated.

Shade: Transparent PMMA with white decorative ring. UV-resistant.

DIMENSIONS

Lamp housing: Ø460 mm. Height 107 mm
Weight: 8,6kg

LUMINOUS FLUX

Luminous efficacy: 122 Lm/W
Lumen, 80 Ra: 3000K: >6466Lm. 4000K: >7112Lm

LIGHT SOURCE

LED type: Philips Fortimo FastFlex
Operational life: >120.000 hours at Ta 25° C. L80B10
Total consumption: Standard 20W (max 53W)
Colour temperature: 2200K, 2700K, 3000K, 4000K
Colour rendering: CRI >80 (Std.), CRI >70 (Opt.)
Colour accuracy: 5 steps SDCM

DRIVER

Driver type: Philips Xitanium
Operational life: >100.000 hours
Surge protection: >10 kV
Control: Compatible with Dynadimmer, 1-10V by default. Compatible with DALI, Zhaga book 18 as optional extra.

INSTALLATION

For arm mounting. Fits Ø48 mm spigot.

CONNECTION

Comes with med 10 m cable. 2x1 mm²

CLASSIFICATION

IP65, IK10, Insulation safety class II

CERTIFICATIONS

MIRUM L1400 is Dark Sky Approved by DarkSky International. 3000k or lower must be selected to meet the DarkSky International certification criteria.

Lampas



Certified by DarkSky.org

Lampas.com